

PRIME

AIR-COOLED

Model	Voltage	Output LP			Output Natural Gas			CB Amps	Engine	Shipping	
		Watts	kVa	Amps	Watts	kVa	Amps			Weight	Dimensions (in)
PSS8B2W	120/240	6,720	6.7	28	6,080	6	25.3	25	B&S Vanguard	400 lbs	45 x 30 x 32
PSS8B2W SOLAR	120/240	6,720	6.7	28	6,080	6	25.3	25	B&S Vanguard	460 lbs	49 x 35 x 35
PSS12H2W	120/240	9,600	9.6	40	8,000	8	33	40	Honda GX690	483 lbs	48 x 32 x 35
PSS12H2W SOLAR	120/240	9,600	9.6	40	8,000	8	33	40	Honda GX690	532 lbs	48 x 32 x 35

LIQUID-COOLED

Model	Voltage	Output ⁽¹⁾ LP			Output ⁽¹⁾ Natural Gas			CB Amps	Engine	Shipping Housed	
		Watts	kVa	Amps	Watts	kVa	Amps			Weight (lbs)	Dimensions (in)
PSS30	120/240	25,200	25	105	24,300	24	101	125	FORD 2.5L	1,570	86 x 40 x 51

Notes: (1) Output information is single phase, see spec sheets for 3-phase information.

DR/RP SERIES

Model	Engine		Shipping			
	Model	Tier	Weight Open	Weight Housed	Open Dimensions (in)	Housed Dimensions (in)
DR1214	Isuzu 3CE1	IV Final	916 lbs	1,946 lbs	63 x 34 x 34	75 x 34 x 45
RP50	FPT F5	IV Final	3,350 lbs	4,150 lbs	100 x 50 x 65	100 x 60 x 70

Note: RP models are dedicated voltage with no receptacle packages.



TOWABLE

Model	Watts	Voltage	Engine		Tank Size	Receptacles	Shipping	
			Model	Tier			Weight	Dimensions (in)
DR12	11,250	Dedicated	Isuzu 3CE1	IV Final	54 Gal	Standard	2,940 lbs	131 x 54 x 78
RP50	47,500	Switchable	FPT F5	IV Final	95 Gal	Standard	4,500 lbs	150 x 71 x 88

