

STANDBY



AIR-COOLED

Model	Voltage	Output LP			Output Natural Gas			CB Amps	Engine	Shipping	
		Watts	kVa	Amps	Watts	kVa	Amps			Weight	Dimensions (in)
PSS8B2W	120/240	8,400	8.4	35	7,600	7.6	32	35	B&S Vanguard	400 lbs	45 x 30 x 32
PSS8B2W SOLAR	120/240	6,720 ⁽¹⁾	6.7	28	6,080 ⁽¹⁾	6	25.3	25	B&S Vanguard	460 lbs	49 x 35 x 35
PSS12H2W	120/240	12,000	12	50	10,000	10	41	50	Honda GX690	484 lbs	48 x 32 x 35
PSS12H2W SOLAR	120/240	9,600 ⁽¹⁾	9.6	40	8,000 ⁽¹⁾	8	33	40	Honda GX690	532 lbs	48 x 32 x 35
PSS20B2W	120/240	17,000	17	71	15,000	15	52	80	B&S Vanguard	878 lbs	61 x 38 x 43

Notes: (1) Rated output reflects prime power derate.



LIQUID-COOLED

Model	Voltage	Output ⁽¹⁾ LP			Output ⁽¹⁾ Natural Gas			CB Amps	Engine	Shipping Housed	
		Watts	kVa	Amps	Watts	kVa	Amps			Weight (lbs)	Dimensions (in)
PSS21	120/240	21,000	21	88	21,000	21	88	90	FORD 2.5L	1,486	86 x 40 x 51
PSS30	120/240	28,000	28	116	27,000	27	112	125	FORD 2.5L	1,570	86 x 40 x 51
PSS60	120/240	56,000	56	233	55,000	55	229	250	GM 5.7L	2,390	110 x 40 x 60
PSS90	120/240	80,000	80	333	90,000	90	375	350	GM 5.7L T	2,964	113 x 47 x 67
PSS150	120/240	120,000	120	500	125,000	150	625	600	PSI 8.8L TAC	5,500	132 x 53 x 72

Notes: (1) Output information is single phase, see spec sheets for 3-phase information.

For more than 150kW, WINCO offers paralleling options.

